

Metal Conduit System



// SPECIALITY
IS OUR
STRENGTH

//



ICMS

Industrial Cable Management System Co.



Industrial Cable Management System Co.

www.icmstray.com

INTRODUCTION

INDUSTRIAL CABLE MANAGEMENT SYSTEMS COMPANY (ICMS) is a pioneer in the field of quality cable management systems in the state of Qatar.

ICMS rigid conduits offer a reliable solution for both new build and refurbishment contracts. The wide range of fittings means that almost any installation can be specified with confidence. Manufactured from high quality steel, ICMS rigid conduits and accessories are capable of withstanding extreme conditions on site and exceeds the stringent requirements of established international standards.

Our advanced manufacturing facilities and the assistance of highly qualified professionals ensure us to provide superior quality products at competitive prices. ICMS products are designed in conformation with an international quality standard such as BS 4568/BS EN 50086/ BS EN 61386 / BS 31/BS 4662 and BS 731 are appreciated for dimensional accuracy and perfect finish.

It's products are approved by various utilities and major consulting offices; further reconfirming the fact that industrial cable management systems satisfies your definition of quality in every aspect of its business activity, having the following certification.

Metallic Steel Conduit

- ICMS produce the quality of steel conduits and fittings that are protect the cable and electrical wire from damage.

Features:

- Hot-dip galvanized exterior and interior provides anti-corrosion and abrasion.
- High grade mild strip steel provides durability and endurance.
- Maintains ductility, providing easy bending, cutting and joining.

Material and Finish:

- Steel finished to hot dip galvanized inside and outside (Class 4 finish).

Standard:

- BS 31
- BS 4568-1
- BS EN 50086-1
- BS EN 50086-2-1
- BS EN 61386-21

Straight length ordering Way;



Part Number	Outside diameter(mm)	Nominal wall thickness (mm)	Length(m)	Approximate weight per length (kgs)
SC-20-H	20	1.6	3.75	2.72
SC-25-H	25	1.6	3.75	3.46
SC-32-H	32	1.6	3.75	4.63
SC-38-H	38	1.8	3.75	6.13
SC-50-H	50	2.0	3.75	9.15

Conduit Fittings

Terminal



Part Number	Size(mm)	Pcs/Carton
FR020	20	100
FR025	25	100
FR032	32	50
FR038	38	20
FR050	50	20
Material: Malleable iron Finish: Hot dip galvanized		

Angle



Part Number	Size(mm)	Pcs/Carton
FA020	20	100
FA025	25	100
FA032	32	50
FA038	38	20
FA050	50	20
Material: Malleable iron Finish: Hot dip galvanized		

Through



Part Number	Size(mm)	Pcs/Carton
FS020	20	100
FS025	25	100
FS032	32	50
FS038	38	20
FS050	50	20
Material: Malleable iron Finish: Hot dip galvanized		

Tee



Part Number	Size(mm)	Pcs/Carton
FT020	20	100
FT025	25	100
FT032	32	50
FT038	38	20
FT050	50	10
Material: Malleable iron Finish: Hot dip galvanized		

Intersection




Part Number	Size(mm)	Pcs/Carton
FI020	20	100
FI025	25	100
FI032	32	50
FI038	38	10
FI050	50	10
Material: Malleable iron Finish: Hot dip galvanized		

Branch two way (U)




Part Number	Size(mm)	Pcs/Carton
FU020	20	100
FU025	25	100
FU032	32	50
Material: Malleable iron Finish: Hot dip galvanized		

Twin through way (H)




Part Number	Size(mm)	Pcs/Carton
FH020	20	100
FH025	25	100
FH032	32	50
Material: Malleable iron Finish: Hot dip galvanized		

Branch three way (Y)



Part Number	Size(mm)	Pcs/Carton
FY020	20	100
FY025	25	100
FY032	32	50
Material: Malleable iron Finish: Hot dip galvanized		

Back outlet




Part Number	Size(mm)	Pcs/Carton
FO020	20	100
FO025	25	100
FO032	32	50
Material: Malleable iron Finish: Hot dip galvanized		

Terminal with back outlet




Part Number	Size(mm)	Pcs/Carton
FOR020	20	100
FOR025	25	100
FOR032	32	50
Material: Malleable iron		Finish: Hot dip galvanized

Angle with back outlet



Part Number	Size(mm)	Pcs/Carton
FOA020	20	100
FOA025	25	100
FOA032	32	50
Material: Malleable iron		Finish: Hot dip galvanized

Through with back outlet



Part Number	Size(mm)	Pcs/Carton
FOS020	20	100
FOS025	25	100
FOS032	32	50
Material: Malleable iron		Finish: Hot dip galvanized

Tee with back outlet



Part Number	Size(mm)	Pcs/Carton
FOT020	20	100
FOT025	25	100
FOT032	32	50
Material: Malleable iron		Finish: Hot dip galvanized

Intersection with back outlet




Part Number	Size(mm)	Pcs/Carton
FOI020	20	100
FOI025	25	100
FOI032	32	50
Material: Malleable iron		Finish: Hot dip galvanized

Branch two way (U) with back outlet



Part Number	Size(mm)	Pcs/Carton
FOU020	20	100
FOU025	25	100
FOU032	32	50
Material: Malleable iron		Finish: Hot dip galvanized

Twin through way (H) with back outlet



Part Number	Size(mm)	Pcs/Carton
FOH020	20	100
FOH025	25	100
FOH032	32	50
Material: Malleable iron		Finish: Hot dip galvanized

Branch three way (Y) with back outlet



Part Number	Size(mm)	Pcs/Carton
FOY020	20	100
FOY025	25	100
FOY032	32	50
Material: Malleable iron		Finish: Hot dip galvanized

Dome lid



Part Number	Size(mm)	Pcs/Carton
DL-20H	20	300
DL-25H	25	300
Material: Malleable iron		Finish: Hot dip galvanized

Circular box extension ring



Part Number	Size(mm)	Pcs/Carton
FER2025-13	13	300
FER2025-16	16	300
FER2025-20	20	300
FER2025-25	25	200
FER2025-32	32	120
FER2025-38	38	120
Material: Malleable iron		Finish: Hot dip galvanized

Looping box



Part Number	Size(mm)	Pcs/Carton
FL020-1	20	120
FL020-2	20	120
FL020-3	20	120
FL020-4	20	120
FL025-1	25	100
FL025-2	25	100
Material: Malleable iron		Finish: Hot dip galvanized

Hook



Part Number	Size(mm)	Pcs/Carton
HK13-H	20&25	300
Material: Malleable iron		Finish: Hot dip galvanized

Rubber gasket



Part Number	Size(mm)	Pcs/Carton
RG13	25&20	2500
RG05	32	500
Material: Rubber		

Circular box cover



Part Number		Size(mm)	Pcs/Carton
Hot Dip Galvanized	Electro Galvanized		
CC13-H	CC13-G	20&25	500
CC05-H	CC05-G	32	250
Material: Steel			

90 Deg. normal bend



Part Number	Size(mm)	Pcs/Carton
B9020	20	100
B9025	25	60
B9032	32	50
B9038	38	40
B9050	50	20
Material: Steel		Finish: Hot dip galvanized

Bends

Inspection elbow



Part Number	Size(mm)	Pcs/Carton
IL20	20	100
IL25	25	100
IL32	32	50
Material: Malleable iron		Finish: Hot dip galvanized

Inspection tee



Part Number	Size(mm)	Pcs/Carton
IT20	20	100
IT25	25	100
IT32	32	50
Material: Malleable iron		Finish: Hot dip galvanized

Inspection bend



Part Number	Size(mm)	Pcs/Carton
IB20	20	100
IB25	25	100
IB32	32	50
Material: Malleable iron		Finish: Hot dip galvanized

Coupling



Part Number	Size(mm)	Pcs/Carton
C120	20	1000
C125	25	500
C132	32	400
C138	38	300
C150	50	100
Material: Steel		Finish: Hot dip galvanized

Expansion coupling



Part Number	Size(mm)	Pcs/Carton
C320	20	200
C325	25	200
C332	32	50
C338	38	100
C350	50	50
Material: Steel		Finish: Hot dip galvanized

Short nipple



Part Number	Size(mm)	Pcs/Carton
N20S	20	1000
N25S	25	750
N32S	32	500
Material: Steel		Finish: Hot dip galvanized

Long nipple




Part Number	Size(mm)	Pcs/Carton
N20L	20	100
N25L	25	75
N32L	32	50
Material: Steel		Finish: Hot dip galvanized

Coupling with earthing lug



Part Number	Size(mm)	Pcs/Carton
C420	20	1000
C425	25	500
C432	32	400
Material: Steel		Finish: Hot dip galvanized

Flange coupling with lead washer & long male bush




Part Number	Size(mm)	Pcs/Carton
C220	20	200
C225	25	200
C232	32	100
Material: Steel & Malleable Iron (Flange coupling and Lead washer), Brass (Long male Bush)		Finish: Hot dip galvanized

Plug



Part Number	Size(mm)	Pcs/Carton
SPH20-H	20	1000
SPH25-H	25	500
SPH32-H	32	500
Material: Malleable iron		Finish: Hot dip galvanized

Reducer



Part Number	Size(mm)	Pcs/Carton
R12025	20x25	1000
R12532	25x32	500
R12032	20x32	500
Material: Malleable iron		Finish: Hot dip galvanized

Stopping plug slotted head



Part Number	Size(mm)	Pcs/Carton
SPS20-B	20	2000
SPS25-B	25	1000
SPS32-B	32	500
Material: Brass		

Bushes

Male bush short



Part Number	Size(mm)	Pcs/Carton
MB20S	20	2000
MB25S	25	1000
MB32S	32	1000
MB38S	38	500
MB50S	50	250
Material: Brass		

Male bush long



Part Number	Size(mm)	Pcs/Carton
MB20L	20	2000
MB25L	25	1000
MB32L	32	500
MB38L	38	300
MB50L	50	200
Material: Brass		

Female bush



Part Number	Size(mm)	Pcs/Carton
FB20	20	3000
FB25	25	3000
FB32	32	1500
FB38	38	500
FB50	50	500
Material: Brass		

Saddles and Locknuts

Half saddle



Part Number		Size(mm)	Pcs/Carton
Hot Dip Galvanized	Electro Galvanized		
HS20H	HS20G	20	2000
HS25H	HS25G	25	2000
HS32H	HS32G	32	1500
Material: Steel			

Plain saddle



Part Number		Size(mm)	Pcs/Carton
Hot Dip Galvanized	Electro Galvanized		
PS20H	PS20G	20	2000
PS25H	PS25G	25	1500
PS32H	PS32G	32	1000
Material: Steel			

Bar saddle



Part Number		Size(mm)	Pcs/Carton
Hot Dip Galvanized	Electro Galvanized		
BS20H	BS20G	20	1000
BS25H	BS25G	25	1000
BS32H	BS32G	32	500
BS38H	BS38G	38	400
BS50H	BS50G	50	200
Material: Steel			

Distance saddle



Part Number	Size(mm)	Pcs/Carton
DS20H	20	500
DS25H	25	300
DS32H	32	200
DS38H	38	160
DS50H	50	120
Material: Steel		Finish: Hot dip galvanized

Hexagonal locknut-Light



Part Number		Size(mm)	Pcs/Carton
Hot Dip Galvanized	Electro Galvanized		
LN203-H	LN203-G	20	3000
LN253-H	LN253-G	25	2000
LN323-H	LN323-G	32	1500
LN383-H	LN383-G	38	1000
LN503-H	LN503-G	50	500
Material: Steel			

Hexagonal locknut-Heavy



Part Number		Size(mm)	Pcs/Carton
Hot Dip Galvanized	Electro Galvanized		
LN206-H	20	2000	2000
LN256-H	25	1000	1500
LN326-H	32	1000	1000
Material: Steel		Finish: Hot dip galvanized	

Locking ring



Part Number		Size(mm)	Pcs/Carton
Hot Dip Galvanized	Electro Galvanized		
LN206-H	20	2000	2000
LN256-H	25	1000	2000
LN326-H	32	1000	1500
Material: Steel		Finish: Hot dip galvanized	

Flexible conduit

Standard:

- BS 731
- BS EN 50086-2-3
- BS EN 61386-23

Flexible Galvanised Steel Conduit (FSC)



Material : Galvanised steel (Uncovered type)
Flexibility : Very high flexibility
Fatigue life: Very high fatigue life
Temperature range: -50°C to +250°C
Fire performance: Low fire hazard, flame retardant, zero halogen.

Part Number	Nominal Conduit Size (mm)	Inside Dia (mm)	Outside Dia (mm)	Coil Length (m)
FSC-20	20	16.9	20.5	10/30/50
FSC-25	25	21.4	25.0	10/30/50
FSC-32	32	28.1	32.0	10/20
FSC-50	50	48.4	53.0	10/20
When ordering, eg FSC-32-Coil length.				


Flexible PVC coated conduit (FCC)



Material: Galvanised steel core with PVC coated
Colour: Black
IP rating: **IP54**
Flexibility: Very high flexibility
Fatigue life: Very high fatigue life
Temperature range: -25°C to +90°C

Part Number	Nominal Conduit Size (mm)	Inside Dia (mm)	Outside Dia (mm)	Coil Length (m)
FCC-20	20	17.0	21.2	10/30/50
FCC-25	25	21.1	25.7	10/30/50
FCC-32	32	28.4	33.0	10/20
FCC-50	50	48.2	64.5	10/20
When ordering, eg FCC-25-Coil length.				

Flexible low fire hazard conduit (FLZH)



Material: Galvanised steel core with PVC coated
Colour: Black
IP rating: IP54
Flexibility: Medium flexibility
Fatigue life: Medium fatigue life
Temperature range: -25°C to +90°C

Part Number	Nominal Conduit Size (mm)	Inside Dia (mm)	Outside Dia (mm)	Coil Length (m)
FLZH-20	20	17.0	21.2	10/20
FLZH-25	25	21.1	25.7	10/30
FLZH-32	32	28.4	33.0	10/30
FLZH-50	50	48.2	54.9	10/30
When ordering, eg FLZH-20-Coil length.				

Flexible stainless steel conduit (FSSC)



Material: Stainless steel
Flexibility: Very high flexibility
Fatigue life: Very high fatigue life
Abrasion resistance: High
Fire performance: Flame retardant, zero halogen.

Part Number	Nominal Conduit Size (mm)	Inside Dia (mm)	Outside Dia (mm)	Coil Length (m)
FSSC-20	20	17.0	20.2	10/30
FSSC-25	25	21.1	24.7	10/30
FSSC-32	32	28.4	32.0	10/20
FSSC-50	50	48.4	53.0	10/20
When ordering, eg FSSC-25-Coil length.				

Flexible liquid tight conduit (FLTC)



Material: Galvanised steel core with PVC coated
 Colour: Black
 Flexibility: Medium flexibility
 IP rating: IP66
 Temperature range: -5°C to +100°C

Part Number	Nominal Conduit Size (mm)	Inside Dia (mm)	Outside Dia (mm)	Coil Length (m)
FLTC-20	20	15.9	21.1	10/20/30
FLTC-25	25	21.0	26.4	10/20/30
FLTC-32	32	26.7	33.1	10/20
FLTC-50	50	40.4	47.5	10/20

When ordering, eg FLTC-20-Coil length.

Flexible metallic conduit fittings

Male adaptor with screw (FAS)



Straight fitting with fixed external thread.
 Material/Finish: Brass (BR)

Part Number	Metric Thread Size
FAS-20-M/F	M20
FAS-25-M/F	M25
FAS-32-M/F	M32
FAS-50-M/F	M50

When ordering, eg FAS-32-Material finish

Fixed type (FFE)



Straight fitting with fixed external thread.
 Material/Finish: Brass nickel plated (NI)

Part Number	Metric Thread Size
FFE-20-M/F	M20
FFE-25-M/F	M25
FFE-32-M/F	M32
FFE-50-M/F	M50

When ordering, eg FFE-32-Material finish

Swivel type (FSE)



Straight fitting with swivel external thread.
 Material/Finish: Brass nickel plated (NI)

Part Number	Metric Thread Size
FSE-20-M/F	M20
FSE-25-M/F	M25
FSE-32-M/F	M32
FSE-50-M/F	M50

When ordering, eg FSE-32-Material finish

Liquidtight male connector (FLT) - IP66



Liquidtight straight fitting with external thread.
 Material/Finish: Brass nickel plated (NI)
 IP Rating: IP66 -For covered steel conduit/liquid tight conduit.

Part Number	Metric Thread Size
FLT-20-M/F	M20
FLT-25-M/F	M25
FLT-32-M/F	M32
FLT-50-M/F	M50

When ordering, eg FLT-20-Material finish

Liquidtight male connector (FWP) - IP65



Liquidtight Straight fitting with external thread.
 Material/Finish: Die cast zinc(DC)
 IP Rating: IP65 -For covered steel conduit/Liquid tight conduit.

Part Number	Metric Thread Size
FFE-20-M/F	M20
FFE-25-M/F	M25
FFE-32-M/F	M32
FFE-50-M/F	M50

When ordering, eg FFE-32-Material finish

Lock nut (FLN)



Material/Finish: Brass nickel plated (NI)
 /Hot dip galvanized(HG) /
 Zinc plated(GI).

Part Number	Metric Thread Size
FLN-20-M/F	M20
FLN-25-M/F	M25
FLN-32-M/F	M32
FLN-50-M/F	M50

When ordering, eg FLN-25-Material finish

Flexible non-metallic conduit system

Flexible polyamide conduit (FPC)



Material: Polyamide (nylon) 6
 Color: Black.
 Flexibility: High flexibility
 Fatigue life: high fatigue Life
 Fire performance: Self extinguishing, Halogen free.

Part Number	Nominal Conduit Size (mm)	Inside Dia (mm)	Outside Dia (mm)	Coil Length (m)
FPC-21	21	16.8	21.2	50
FPC-28	28	22.2	28.5	50
FPC-34	34	27.9	34.5	20
FPC-54	54	46.9	54.5	20
When ordering, eg FPC-28-Coil length				

Flexible non-metallic conduit fitting

Straight Fitting (FSF)



Straight fitting with thread.
 Material: Polyamide (nylon) 6, Black (BL)

Part Number	Metric Thread Size
FSF-21-M/F	M20
FSF-28-M/F	M25
FSF-34-M/F	M32
FSF-54-M/F	M50
When ordering, eg FSF-34-Material finish	

Switch and Socket Boxes

One Gang



Material : Steel
Finish : Galvanized
Standard : BS4662, BS EN 60670-1

SR.No.	PART No.	SIZE(LxWxHxt), mm	K/O's
1	SSB-1-25-09	72x72x25x0.9	12x20mm
2	SSB-1-25-11	72x72x25x1.1	12x20mm
3	SSB-1-35-09	72x72x35x0.9	7x20mm, 4x25mm
4	SSB-1-35-11	72x72x35x1.1	7x20mm, 4x25mm
5	SSB-1-47-09	72x72x47x0.9	9x20mm, 1x25mm
6	SSB-1-47-11	72x72x47x1.1	9x20mm, 1x25mm

Two Gang



Material : Steel
Finish : Galvanized
Standard : BS4662, BS EN 60670-1

SR.No.	PART No.	SIZE(LxWxHxt), mm	K/O's
1	SSB-2-25-09	132x72x25x0.9	16x20mm
2	SSB-2-25-11	132x72x25x1.1	16x20mm
3	SSB-2-35-09	132x72x35x0.9	13x20mm, 3x25mm
4	SSB-2-35-11	132x72x35x1.1	13x20mm, 3x25mm
5	SSB-2-47-09	132x72x47x0.9	10x20mm, 6x25mm
6	SSB-2-47-11	132x72x47x1.1	10x20mm, 6x25mm

Adaptable Box



Material/Finish(M/F)
• PG: Pre galvanized Steel
• HG: Hot dip galvanized

SR.No.	PART No.	SIZE (mm)
1	AB-75-75-37.5-M/F	75X75X37.5
2	AB-75-75-50-M/F	75X75X50
3	AB-100-100-37.5-M/F	100X100X37.5
4	AB-100-100-50-M/F	100X100X50
5	AB-100-100-75-M/F	100X100X75
6	AB-150-150-75-M/F	150X150X75
7	AB-150-150-100-M/F	150X150X100
8	AB-225-225-75-M/F	225X225X75
9	AB-225-225-100-M/F	225X225X100
10	AB-300-300-100-M/F	300X300X100



Nemko Ltd

TEST CERTIFICATE

No. : C19 / 52927

Client

**Industrial Cable Management System
Co. W.L.L. (ICMS)**

Area 92, Street No. 710, Gate No. 532,
P.O. Box 22108, Mesaieed, Qatar

Client contact

Mr. Biju Jose N

Item(s) tested

Metal flush mounted wall boxes
Models: SSB-x-xx-xx (see page 2)
Rated : N/A

Specification(s) to which above
unit(s) have been tested and
compliance confirmed

**BS EN 60670-1: 2005 +A1: 2013 and BS 4662:
2006 +A1: 2009* and deemed to comply**

Date of issue

11 July 2019

*Compliance with a Harmonised European Standard
also gives the presumption of compliance with the
Principal Elements of the Safety Objectives of the
Low Voltage Directive 2014/35/EU*

Signed

Bunmi Phillips
(Certifying Officer)

Relating to Project File(s) held at
Nemko Ltd

52927

To be read in conjunction
with page 2 attached



*BS 4662 not UKAS



Form No: QF102-1
Issue No: 6
Issue Date: 08.03.16

**Nemko Ltd**

Certificate No:	C19 / 52927
Client:	Industrial Cable Management System Co. W.L.L. (ICMS)

THIS CERTIFICATE APPLIES ONLY TO THE PARTICULAR SAMPLE UNIT(S) TESTED AND TO THE SPECIFIC TESTS CARRIED OUT AS DETAILED IN THE PROJECT FILE HELD AT NEMKO LTD.

THIS TEST CERTIFICATE DOES NOT COVER ELECTROMAGNETIC COMPATIBILITY.

IT SHOULD BE NOTED THAT ONLY A LIMITED NUMBER OF UNITS HAVE BEEN TESTED. IT IS THEREFORE ESSENTIAL FOR THE MANUFACTURER OR SUPPLIER OF THIS PRODUCT TO ENSURE THAT THE QUALITY OF ALL PRODUCTION UNITS IS OF THE SAME STANDARD AS THAT OF THE SAMPLE(S) CHECKED

Models covered by this certificate			
Model no.	Description	Model no.	Description
SSB-1-35-09	1 gang 35mm deep (0.9mm)	SSB-2-35-09	2 gang 35mm deep (0.9mm)
SSB-1-47-09	1 gang 47mm Deep (0.9mm)	SSB-2-47-09	2 gang 47mm Deep (0.9mm)
SSB-1-35-11	1 gang 35mm Deep (1.1mm)	SSB-2-35-11	2 gang 35mm Deep (1.1mm)
SSB-1-47-11	1 gang 47mm Deep (1.1mm)	SSB-2-47-11	2 gang 47mm Deep (1.1mm)

Condition / number of test sample(s) : Good / 64 Serial Number(s) : -

Notes relating to this Certificate: - none

Project History: -

<u>Job Number</u>	<u>Sample received</u>	<u>Job Completion Date</u>	<u>Summary of work carried out</u>
52927	11-June-2019	11-July-2019	Full testing to BS EN 60670-1: 2005 +A1: 2013 and BS 4662: 2006 +A1: 2009

***** END OF CERTIFICATE *****





EUROPEAN INSPECTION AND CERTIFICATION COMPANY S.A.

CERTIFICATE OF CONFORMITY

FULLNESS EXAMINATION OF TECHNICAL FILE

Certificate No.	: LVD.0092
Issue Date	: 06/07/2020
Expiry Date	: 05/07/2025
Applicant	: INDUSTRIAL CABLE MANAGEMENT SYSTEM Co. W.L.L.
(Name & Address)	: Area 92, Street No. 710, Gate No. 532, PO Box 22108, Qatar
Manufacturer	: Same as applicant
(Name & Address)	
Test Report Ref	: ITC/TEST/NN/2003/02-A, ITC/TEST/NN/2003/02-B
TCF No.	: ICMS/TCF/01
Product Description	: FLEXIBLE PVC COATED CONDUIT
Model(s)	: FCC-20, FCC-25
Directive(s)	: Low Voltage Directive (2014/35/EU)
Standard(s)	: BS EN 61386-1:2008+A1:2019, BS EN 61386-23:2004+A11:2010

This is to certify that, upon the relevant application of the above-mentioned company, EUROCERT S.A. as Third Party Authority has reviewed the Technical Construction File of the described product which found to fulfil the basic health and safety prerequisites of above mentioned Directive(s).

Note:

- The manufacturer should issue a Declaration of Conformity according to the basic requirements of the applicable and relevant directives.
- The CE marking can be affixed on the above-mentioned product with the manufacturer's responsibility, if all relevant and applicable directives are complied with.
- All modifications to the Technical File should be first submitted to the Third Party Inspection Authority to ensure further validity of this attestation.
- This certificate is valid only for the product and configuration described and in conjunction with the technical data detailed above.

Please check the validity of the certificate from our website using the password **ZKhwsmB1**



Third Party Authority Stamp

On Behalf of EUROCERT



GEORGE NISIFONIOS
Director of Development

40 CHESS ST. & LINDOSIACTE, 144 52 PAFTHANORIOS, ATHENS, GREECE
Tel: ++30 210 62 52 495 - 30 210 62 53 607 - Fax: ++30 210 62 03 018
Internet: www.eurocert.gr - info@eurocert.gr



Blank lined area for notes or specifications.



Industrial Cable Management Systems Co.

+974 4444 6246 | Fax: +974 4444 6242

www.icmstray.com